

Rental Outdoor LED Screen Technical Parameters

Pixel(mm)	P3.91	P3.91	P4.81	P4.81
Module Size (mm)	250*250	250*250	250*250	250*250
Module Resolution	64*64	64*64	52*52	64*64
Scan	1/16	1/16	1/13	1/16
Pixel Configuration	1R1G1B	1R1G1B	1R1G1B	1R1G1B
LED Type	SMD1919	SMD1919	SMD1919	SMD1919
Cabinet Size	500*500	500*1000	500*500	500*1000
Cabinet Resolution	128*128	128*256	104*104	104*208
Brightness(cd/m2)	800-3000	800-3000	800-3000	800-3000
Pixel Density (dot/m2)	65536	65536	43264	43264
Max Power Consumption (W/m2)	260W	510W	260W	510W
Ave Power Consumption (W/m2)	90W	170W	100W	170W
Cabinet Weight(KG)	7KG	13KG	7KG	13KG
Cabinet Material	Die Aluminum	Die Aluminum	Die Aluminum	Die Aluminum
Protection Degree	IP65	IP65	IP65	IP65
Refresh Rate (Hz)	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Refresh Rate (Hz)	3840	3840	3840	3840
Horizontal Degree	140	140	140	140
Vertical Degree	120	120	120	120
Working Voltage (V)	AC110V-240V	AC110V-240V	AC110V-240V	AC110V-240V
Working Temperature	-20-60℃	-20-60℃	-20-60℃	-20-60℃
Storage Humidity	40%-60% RH	40%-60% RH	40%-60% RH	40%-60% RH
Liftspan	≥100000Hours	≥100000Hours	≥100000Hours	≥100000Hours